Chapter 12. Rotational Dynamics

As we did for linear (or translational) motion, we studied kinematics (motion without regard to the cause) and then dynamics (motion with regard to the cause), we now proceed in a similar fashion

□ We know that forces are responsible for linear motion

We will now see that rotational motion is caused by torques

□ Consider a wrench of length L=r



r is called the lever arm. Must always be perpendicular to the force

If the force is not perpendicular to the level arm, we need to find the component that is perpendicular (either the force or the lever arm)

F sin ϕ $\tau = rF \sin \phi$

If $\phi = 0$, then the torque is zero

□ Therefore, torques (force times length) are responsible for rotational motion

r

Φ

Newton's 2nd Law for Rotational Motion

 $F = F_{t}$

m

r

- The torque for a pointparticle of mass m a distance r from the rotation axis is
- $\tau = rF_{t}$ $F_{t} = ma_{t}, a_{t} = r\alpha$ $\Rightarrow \tau = ma_{t}r = mr^{2}\alpha$ Axis of rotation

□ Define I = mr^2 = Moment of Inertia for a point particle; a scalar, units of kg m^2

□ A rigid body is composed of many, many particles

of mass m_i which are r_i from the axis of rotation

 Each of these masses creates a torque about the axis of rotation
Rotation axis

 $\tau_1 = m_1 r_1^2 \alpha$ $\tau_2 = m_2 r_2^2 \alpha$

□ Sum up all torques due to all particles

 $\sum \tau_{i} = \sum m_{i} r_{i}^{2} \alpha$ $I = \sum m_{i} r_{i}^{2}$ $\sum \tau = I \alpha$

 $\ensuremath{^\alpha}$ is the same for all particles

I =moment of inertia for the rigid body. It is different for different shaped objects and for different axes of rotation. Table 12.2.

 m_2

□ For a thin rod of mass M and length L

 $I = \frac{1}{12}ML^2$

□ The last equation is Newton's 2nd Law for rotation. Compare to the translational form

 $I = \frac{1}{3}ML^2$

$$\sum \vec{\tau} = I \vec{\alpha} \iff \sum \vec{F} = m \vec{a}$$

Example Problem

L/2

A rotating door is made of 4 rectangular panes each with a mass of 85 kg. A person pushes on the outer edge of one pane with a force of 68 N, directed perpendicular to the pane. Determine the door's α .

Given: L = 1.2 m, m_{pane}=85 kg, F=68 N $\Sigma \tau = I\alpha$ $FL = I\alpha \Rightarrow \alpha = \frac{FL}{I}$

From Fig. 9.18, moment of inertia for a thin rectangular rod is (same as a thin sheet) Since there are 4 panes. $I_{pane} = \frac{1}{3}ML^2 \implies I_{door} = \frac{4}{3}ML^2$ $\alpha = \frac{FL}{I} = \frac{FL}{\frac{4}{3}ML^2}$ $\alpha = \frac{3F}{4ML} = \frac{3(68 \text{ N})}{4(85 \text{ kg})(1.2 \text{ m})} = 0.50 \frac{\text{N}}{\text{kg m}} = 0.50 \frac{\text{rad}}{\text{s}^2}$

The parallel axis theorem provides a useful way to calculate I about an arbitrary axis. The theorem states that $I = I_{cm} + MD^2$, where I_{cm} is the moment of inertia of an object (of mass M) with an axis that passes through the center of mass and is parallel to the axis of interest. D is the perpendicular distance between the two axes. Now, determine I of a solid cylinder of radius R for an axis that lies on the surface of the cylinder and perpendicular to the circular ends.

Solution: The center of mass of the cylinder is on a line defining the axis of the cylinder

From Table 12.2: $I_{cm} = \frac{1}{2}MR^2$

cm

From the parallel axis theorem with D=R: $I = I_{cm} + MD^2 = \frac{1}{2}MR^2 + MR^2 = \frac{3}{2}MR^2$ Apply to thin rod:



Rotational Work

□ For translational motion, we defined the work as



$W = F_s s = F_t r \theta = (F_t r) \theta^{= r \theta}$

 $W_R = \tau \theta$ Units of N m or J when θ is in radians

Rotational Kinetic Energy

□ For translational motion, the K was defined

 $K = \frac{1}{2}m\mathbf{v}^2$, since $\mathbf{v}_t = r\omega$ $K = \frac{1}{2}m(r\omega)^2 = \frac{1}{2}mr^2\omega^2$ \Box For a point particle I = mr², therefore $K_{rot} = \frac{1}{2}I\omega^2$ • Or for a rigid body $K_{rot} = \frac{1}{2} \sum m_i r_i^2 \omega^2 = \frac{1}{2} I \omega^2 = K_{rot}$ For a rigid body that has both translational and rotational motion, its total kinetic energy is $K_{total} = K + K_{rot} = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2$ □ The total mechanical energy is then $E_{total} = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2 + mgy + \frac{1}{2}kx^2$

Rolling Motion (Tires, Billiards)

B



□ Consider a tire traveling on a road with friction (no skidding) between the tire and road

□ First, review concept of relative velocity. What is the velocity of B as seen by the ground?

 \Box Point B has a velocity v_t with respect to the A

 \Box Now, A (the tire as a whole) is moving to the right with velocity v_{car}



□ What is velocity of C as seen by the ground?



A tire has a radius of 0.330 m, and its center moves forward with a linear speed of 15.0 m/s. (a) What is ω of the wheel? (b) Relative to the axle, what is v_t of a point located 0.175 m from the axle?



Example



A car is moving with a speed of 27.0 m/s. Each wheel has a radius of 0.300 m and a moment of inertia of 0.850 kg m². The car has a total mass (including the wheels) of 1.20×10^3 kg. Find (a) the translational K of the entire car, (b) the total K_{rot} of the four wheels, and (c) the total K of the car.

Solution:

Given: $v_{car} = 27.0 \text{ m/s}$, $m_{car} = 1.20 \times 10^3 \text{ kg}$, $r_w = 0.300 \text{ m}$, $I_w = 0.850 \text{ kg} \text{ m}^2$



A tennis ball, starting from rest, rolls down a hill into a valley. At the top of the valley, the ball becomes airborne, leaving at an angle of 35° with respect to the horizontal. Treat the ball as a thinwalled spherical shell and determine the horizontal distance the ball travels after becoming airborne.

2

1

3

X

4

H

1.8 m

Solution:

Given: $v_0 = 0$, $\omega_0 = 0$, $y_0 = 1.8 \text{ m} = \text{h}$, $y_1 = y_2 = y_4$ = 0, $\theta_2 = 35^{\circ}$, $x_2 = 0$, $I=(2/3)MR^2$

Find: x_4 ?

Method: As there is no "friction" or air resistance in the problem, therefore no non-conservative forces, we can use conservation of mechanical energy $E_{total} = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2 + mgy$ $E_0 = mgh$ $E_{1} = \frac{1}{2}mv_{1}^{2} + \frac{1}{2}I\omega_{1}^{2} + mg(0)$ $E_2 = \frac{1}{2}mv_2^2 + \frac{1}{2}I\omega_2^2 + mg(0) = E_1$



 $\mathbf{v}_{2x} = \mathbf{v}_2 \cos \theta_2 = \mathbf{v}_{4x}$ $v_{2v} = v_2 \sin \theta_2 = -v_{4v}$ $V_{4v} = V_{2v} - g(t_4 - t_2), t_2 = 0$ $-v_{2v} = v_{2v} - gt_4$ $-2\mathbf{v}_{2\nu} = -gt_4 \Longrightarrow |t_4 = 2\mathbf{v}_{2\nu}/g$ $x_4 = x_2 + \frac{1}{2}(v_{2x} + v_{4x})t_4 = v_{2x}t_4$ $x_4 = v_{2x} 2 v_{2y} / g = 2 v_2 \cos \theta_2 v_2 \sin \theta_2 / g$ $x_4 = \frac{2v_2^2 \cos\theta_2 \sin\theta_2}{x_4} = \frac{6gh}{2} \frac{2\cos\theta_2 \sin\theta_2}{2} = \frac{6gh}{2} \frac{2}{2} \cos\theta_2 \sin\theta_2$ 5 g g $12h\cos\theta_2\sin\theta_2$ | $12(1.8)\cos35\sin35$ X_4 $x_{4} = 2.0 \,\mathrm{m}$

 \clubsuit A mass m₁ (=15.0 kg) and a mass m₂ (=10.0 kg) are suspended by a pulley that has a radius R (=10.0 cm) and a mass M (=3.00 kg). The cord has negligible mass and causes the pulley to rotate without slipping. The pulley rotates about its axis without friction. The masses start from rest at a distance h (=3.00 m) part. Treating the pulley as a uniform disk, determine the speeds of the two masses as they pass each other.